





AL FX 315

Food grade extreme pressure grease

Description

High mechanical stability grease, ALFX 315 is recommended for lubricating bearings working under severe conditions of loads and stresses, at weak or medium speed, in the food industry. AL FX 315 is registered by NSF International, in category H1. This indicates that it is authorized for use in incidental contact with food. (N°163387)

Applications

For any lubrication of bearings, joints, heavily loaded parts in the agrofood industry (meet plant, animal feed, beverage etc)

Technical data

Operating temperatures: -20°C to +120°C NLGI Grade: 1 Load: 400 kg

Reference	designation	Packaging				food certificate number
ALFX315FT	GREASE- NLGI3-FOOD GRADE-AL FX 315-DRUM 180KG	FUT		DRUM	180 KG	163387
ALFX31550	GREASE- NLGI3-FOOD GRADE-AL FX 315-KEG 50KG	TONNELET		KEG	50 KG	163387
ALFX315CA	GREASE- NLGI3-FOOD GRADE-AL FX 315-CARTRIDGE 400GR	CARTON	24	CARTOUCHE	400 G	163387

Z.A.E.T - 221, rue Paul Langevin - 60740 Saint-Maximin - FRANCE Tél : +33 (0)3 44 61 76 76 Fax +33 (0)3 44 25 17 78 www.molydal.com