

NS 250

Synthetic lubricant for chains in high temperature environments

Description

High temperatures chain oil, used in severe working conditions (heat, humidity etc).

Applications

For conveyor and quenching chains, paint oven and screen printing ovens. For transmission chains in the wall covering and dying industries, etc. Can be used by immersion, brush application, drip feed or by spraying. Does not carbonise.

Technical data

Operating temperature range: -30°C to +260°C
Viscosity @ 40°C: 180 cst (liquid)
Non-flammable propellant: CO2

Reference	designation	Packaging				food certificate number
NS2505L	CHAIN LUBRICANT-NS 250-JERRYCAN 5L	CARTON	2	JERRYCAN	5 L	
NS250A2	CHAIN LUBRICANT-NS 250-AEROSOL 650/400ML	CARTON	12	AEROSOL	650 / 400 ML	
NS250FT	CHAIN LUBRICANT-NS 250-DRUM 200L	FUT		DRUM	200 L	

Z.A.E.T - 221, rue Paul Langevin - 60740 Saint-Maximin - FRANCE Tél : +33 (0)3 44 61 76 76 Fax +33 (0)3 44 25 17 78 www.molydal.com

The information contained in this document is given in good faith and does not engage our responsability. To know more, pleas check the safety data sheet