



## GRAISSE 3790

### Marine grease

#### Description

Totally insoluble in cold, hot or sea water as well as in steam these properties enable to use it for lubrication of immersed or under severe water spray working equipment's. Highly adhesive and stringy.

#### Applications

For all parts subject to water projection or immersed ; Bearings, rollers, pumps, valves and taps. Water purification plants, hydroelectric power stations, canneries, etc.

#### Technical data

Operating temperature range: -30°C to +140°C

NLGI Grade: 2

Load: 315 kg

Reference	designation	Packaging				food certificate number
379050	ADHESIVE GREAS E-NLGI2-GRAISSE 3790-KEG 50KG	TONNELET		KEG	50 KG	
37905L	ADHESIVE GREAS E-NLGI2-GRAISSE 3790-BUCKET 5L	CARTON	2	BUCKET	5 L	
3790A2	ADHESIVE GREAS E-NLGI2-GRAISSE 3790-AEROSOL 650/400ML	CARTON	12	AEROSOL	650 / 400 ML	
3790B1	ADHESIVE GREAS E-NLGI2-GRAISSE 3790-TIN 1L	CARTON	6	TIN	1 L	
3790CA	ADHESIVE GREAS E-NLGI2-GRAISSE 3790-CARTRIDGE 400GR	CARTON	24	CARTRIDGE	400 G	

